

Technical drawing of a circular structure, likely a cross-section of a pipe or vessel. The drawing includes the following dimensions and labels:

- Overall Diameter:** $\varnothing 2\ 800$
- Horizontal Dimensions (from left edge):** 350, 600, 350, 600, 900.
- Vertical Dimensions (from top edge):** 700, 600, 200, 600, 700.
- Internal Features:**
 - A central vertical dashed line.
 - Four sets of arrows pointing towards the center, labeled 'P'.
 - Four sets of arrows pointing away from the center, labeled 'P'.
 - Four sets of arrows pointing towards the center, labeled 'P'.
 - Four sets of arrows pointing away from the center, labeled 'P'.
 - Four sets of arrows pointing towards the center, labeled 'P'.
 - Four sets of arrows pointing away from the center, labeled 'P'.
 - Four sets of arrows pointing towards the center, labeled 'P'.
 - Four sets of arrows pointing away from the center, labeled 'P'.
- Labels:**
 - \checkmark CS4
 - 3
- Bottom Dimensions (from left edge):** 350, 600, 1000, 600, 250.

Technical drawing of a circular structure, likely a manhole or well, showing dimensions and angles. The drawing includes a top view and a side view.

Top View Dimensions:

- Outer diameter: $\varnothing 800$
- Inner diameter: $\varnothing 500$

Side View Dimensions:

- Overall width: 1250
- Overall height: 1400
- Top section height: 550
- Bottom section height: 550

Angles and Labels:

- Central angle: 37°
- Angle between radial lines: 20°
- Angle between radial lines: 40°
- Angle between radial lines: 25°
- Angle between radial lines: 40°
- Label: ČS4
- Label: Vztlaková pojistka

Technical drawing of a rectangular structure, likely a foundation or slab, showing dimensions and reinforcement details.

Dimensions:

- Overall width: 6400 mm
- Overall height: 6600 mm
- Internal width: 2080 mm
- Internal height: 2080 mm
- Top offset: 100 mm
- Bottom offset: 200 mm
- Left offset: 300 mm
- Right offset: 300 mm

Reinforcement Details:

- Top bars: P
- Bottom bars: P
- Central cross-section: ČS4
- Reinforcement spacing: 218,94 mm (top), 218,24 mm (left), 217,26 mm (right), 214,62 mm (bottom), 212,34 mm (bottom center), 212,54 mm (bottom left corner).

Other Labels:

- 1, 2, 3, 4: Reinforcement points or sections.
- Vzdávková pojistka: Spacing reinforcement.

ČS4 čerpačí stanice
P poklop 600x600

1	DN300	nátok odp. vod do ČS4 – stoka "D"
2	DN300	nátok odp. vod do ČS4 – stoka "F"
3	DN80	výtak z ČS – "V4"
4	2xDN100	kabely – elektro

 **REC.ing**®
REC.ing, spol. s r.o.
Pod Wroclawem 1063
545 01 Nowa Mleczka 12-14 tel. 4
Dł. 2247453761 Tel./fax: 491 426 1

Tato dokumentace včetně všech příloh je duševním vlastnictvím společnosti REC.ing. spol. s r.o.. Jiné osoby (jak fyzické, tak právnické) nejsou bez předchozího výslovného souhlasu oprávněny tuto dokumentaci ani její části jakkoli využívat, kopírovat (ani jiným způsobem rozmnožovat) nebo zpřístupnit dalším osobám. Tato dokumentace slouží k provedení stavby na akci "Kanalizace - Psinice".